### FAIRCHILD

SEMICONDUCTOR TM

### BD241/A/B/C

# Medium Power Linear and Switching Applications

Complement to BD242/A/B/C respectively



1.Base 2.Collector 3.Emitter

### NPN Epitaxial Silicon Transistor


Absolute Maximum Ratings T<sub>C</sub>=25°C unless otherwise noted

Symbol	Parameter	Value	Units
V <sub>CEO</sub>	Collector-Emitter Voltage		
	: BD241	45	V
	: BD241A	60	V
	: BD241B	80	V
	: BD241C	100	V
V <sub>CER</sub>	Collector-Emitter Voltage		
	: BD241	55	V
	: BD241A	70	V
	: BD241B	90	V
	: BD241C	115	V
V <sub>EBO</sub>	Emitter-Base Voltage	5	V
I <sub>C</sub>	Collector Current (DC)	3	А
I <sub>CP</sub>	*Collector Current (Pulse)	5	А
I <sub>B</sub>	Base Current	1	А
P <sub>C</sub>	Collector Dissipation (T <sub>C</sub> =25°C)	40	W
TJ	Junction Temperature	150	°C
T <sub>STG</sub>	Storage Temperature	- 65 ~ 150	°C

### Electrical Characteristics T<sub>C</sub>=25°C unless otherwise noted

Symbol	Parameter	Test Condition	Min.	Тур.	Max.	Units
V <sub>CEO</sub> (sus)	* Collector-Emitter Sustaining Voltage					
	: BD241	I <sub>C</sub> = - 30mA, I <sub>B</sub> = 0	45			V
	: BD241A	-	60			V
	: BD241B		80			V
	: BD241C		100			V
I <sub>CEO</sub>	Collector Cut-off Current : BD241/A	$V_{CE} = 30V, I_{B} = 0$			0.3	mA
	: BD241B/C	$V_{CE} = 60V, I_{B} = 0$			0.3	mA
I <sub>CES</sub>	Collector Cut-off Current : BD241	V <sub>CE</sub> = 45V, V <sub>BE</sub> = 0			0.2	mA
	: BD241A	$V_{CE} = 60V, V_{BE} = 0$			0.2	mA
	: BD241B	$V_{CE} = 80V, V_{BE} = 0$			0.2	mA
	: BD241C	$V_{CE} = 100V, V_{BE} = 0$			0.2	mA
I <sub>EBO</sub>	Emitter Cut-off Current	$V_{EB} = 5V, I_{C} = 0$			1	mA
h <sub>FE</sub>	* DC Current Gain	$V_{CE} = 4V, I_{C} = 1A$	25			
		$V_{CE} = 4V, I_{C} = 3A$	10			
V <sub>CE</sub> (sat)	* Collector-Emitter Saturation Voltage	I <sub>C</sub> = 3A, I <sub>B</sub> = 0.6A			1.2	V
V <sub>BE</sub> (on)	* Base-Emitter ON Voltage	$V_{CE} = 4V, I_{C} = 3A$			1.8	V

©2000 Fairchild Semiconductor International



Rev. A, February 2000

#### TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACEx<sup>™</sup> Bottomless<sup>™</sup> CoolFET<sup>™</sup> CROSSVOLT<sup>™</sup> E<sup>2</sup>CMOS<sup>™</sup> FACT<sup>™</sup> FACT Quiet Series<sup>™</sup> FAST<sup>®</sup> FAST<sup>®</sup> FASTr<sup>™</sup> GTO<sup>™</sup> HiSeC<sup>™</sup> ISOPLANAR<sup>™</sup> MICROWIRE<sup>™</sup> POP<sup>™</sup> PowerTrench<sup>®</sup> QFET<sup>™</sup> QS<sup>™</sup> Quiet Series<sup>™</sup> SuperSOT<sup>™</sup>-3 SuperSOT<sup>™</sup>-6 SuperSOT<sup>TM</sup>-8 SyncFET<sup>TM</sup> TinyLogic<sup>TM</sup> UHC<sup>TM</sup> VCX<sup>TM</sup>

#### DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

#### LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR INTERNATIONAL.

#### As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

#### **PRODUCT STATUS DEFINITIONS**

#### **Definition of Terms**

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Fairchild Semiconductor: