

January 2015

MMPQ6700 Quad NPN and PNP General-Purpose Amplifier

Description

These complementary devices can be used in switches with collector currents of 10 μ A to 100 mA. These devices are best used when space is the primary consideration. Sourced from process 23 and 66. See 2N3904 (NPN) and 2N3906 (PNP) for characteristics.




Figure 1. Device Package




Figure 2. Internal Connection

Ordering Information

Part Number	Top Mark	Package	Packing Method		
MMPQ6700	MMPQ6700	SOIC 16L	Tape and Reel		

Absolute Maximum Ratings(1),(2)

Stresses exceeding the absolute maximum ratings may damage the device. The device may not function or be operable above the recommended operating conditions and stressing the parts to these levels is not recommended. In addition, extended exposure to stresses above the recommended operating conditions may affect device reliability. The absolute maximum ratings are stress ratings only. Values are at $T_A = 25^{\circ}$ C unless otherwise noted.

Symbol	Parameter	Value	Unit
V _{CEO}	Collector-Emitter Voltage	40	V
V _{CBO}	Collector-Base Voltage	40	V
V _{EBO}	Emitter-Base Voltage	5.0	V
I _C	Collector Current - Continuous	200	mA
T _J , T _{STG}	Operating and Storage Junction Temperature Range -55 to 150		°C

Notes:

- 1. These ratings are based on a maximum junction temperature of 150°C.
- 2. These are steady-state limits. Fairchild Semiconductor should be consulted on applications involving pulsed or

Thermal Characteristics(3)

Values are at T_A = 25°C unless otherwise noted.

Symbol	Parameter	Max.	Unit	
D	Total Device Dissipation	1000	mW	
P _D	Derate Above 25°C	8.0	mW/°C	
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient	Effective 4 Dies	125	°C/W
		Each Die	240	°C/W

Note:

3. PCB size: FR-4, 76 mm x 114 mm x 1.57 mm (3.0 inch x 4.5 inch x 0.062 inch) with minimum land pattern size.

Electrical Characteristics

Values are at T_A = 25°C unless otherwise noted.

Symbol	Parameter		Conditions		Min.	Max.	Unit
BV _{CEO}	Collector-Emitter Breakdown Voltage ⁽⁴⁾		I _C = 10 mA, I _B = 0		40		V
BV _{CBO}	Collector-Base Breakdown Voltage		$I_C = 10 \mu A, I_E = 0$		40		V
BV _{EBO}	Emitter-Base Breakdown Voltage		$I_E = 10 \mu A, I_C = 0$		5.0		V
I _{CBO}	Collector Cut-Off Current		$V_{CB} = 30 \text{ V, } I_{E} = 0$			50	nA
I _{EBO}	Emitter Cut-Off Current		V _{EB} = 4.0 V, I _C = 0			50	nA
h _{FE} DC Current Gain ⁽⁴⁾			$V_{CE} = 1.0 \text{ V}, I_{C} = 0.1 \text{ mA}$		30		
	DC Current Gain ⁽⁴⁾		$V_{CE} = 1.0 \text{ V}, I_{C} = 1.0 \text{ mA}$		50		
			V_{CE} = 1.0 V, I_{C} = 10 mA		70		
V _{CE} (sat)	Collector-Emitter Saturation Voltage ⁽⁴⁾		I _C = 10 mA, I _B = 1.0 mA			0.25	V
V _{BE} (sat)	Base-Emitter Saturation Voltage ⁽⁴⁾		I _C = 10 mA, I _B = 1.0 mA			0.9	V
C _{ob}	Output Capacitance		V _{CB} = 5.0 V, f = 100 kHz			4.5	pF
C _{ib}	Input Capacitance		$V_{DE} = 0.5 \text{ V. f} = 100 \text{ kHz}$	PNP		10	nE
				NPN		8.0	- pF
f _T	Current Gain Bandwidth Product		I _C = 10 mA, V _{CE} = 20 V, f = 100 MHz		200		MHz

Note:

4. Pulse test: pulse width \leq 300 μ s, duty cycle \leq 2.0%.

Physical Dimensions 10.00 9.80 8.89 4.00 3.80 6.00 5.6 **PIN ONE** 0.51 **INDICATOR** 1.27 (0.30)**⊕** 0.25 **M** C B A LAND PATTERN RECOMMENDATION 1.75 MAX SEE DETAIL A 1.50 1.25 0.25 0.19 ○ 0.10 C -0.50 0.25 X 45° NOTES: UNLESS OTHERWISE SPECIFIED (R0.10) A) THIS PACKAGE CONFORMS TO JEDEC MS-012, VARIATION AC, ISSUE C. B) ALL DIMENSIONS ARE IN MILLIMETERS. C) DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH AND TIE BAR PROTRUSIONS D) CONFORMS TO ASME Y14.5M-1994 E) LANDPATTERN STANDARD: SOIC127P600X175-16AM F) DRAWING FILE NAME: M16AREV12. **GAGE PLANE** (R0.10) 0.36 **SEATING PLANE** 0.90 0.50 (1.04)

Figure 3. 16-LEAD, SOIC, JEDEC MS-012, 0.150 inch, NARROW BODY

DETAIL A





TRADEMARKS

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

BitSiC™ Green FPS™
Build it Now™ Green FPS™ e-Series™

Current Transfer Logic™ Making Small Speakers Sound Louder DEUXPEED® and Better™

Dual Cool™
EcoSPARK®

EfficientMax™

ESBC™

MicroPak™

MicroPak™

MicroPak™

MicroPak™

MicroPak™

Fairchild®
Fairchild®
Fairchild Semiconductor®
FACT Quiet Series™
FACT®
FAST®
FastvCore™
FETBench™
FPS™

MillerDrive™
MotionGrid®
MTT®
MTx®
MVN®
MVN®
mWSaver®
OptoHiT™
OPTOLOGIC®

OPTOPLANAR®

® PowerTrench® PowerXS™

Programmable Active Droop™

QFET[®]
QS[™]
Quiet Series[™]
RapidConfigure[™]

Saving our world, 1mW/W/kW at a time™

SignalWise™ SmartMax™ SMART START™

Solutions for Your Success™

SPM®
STEALTH™
SuperFET®
SuperSOT™-3
SuperSOT™-6
SuperSOT™-6
SuperSOT™-8
SuperSOT™-8
SuperSOT™-8
SuperSOT™-8
SuperSOT™-8
SuperSOT™-8
SuperSOT™-8
SuperSOT™-8

SYSTEM GENERAL®

TinyBoost®
TinyBuck®
TinyCalc™
TinyLogic®
TINYOPTO™
TinyPower™
TinyPower™
TinyPWM™
TinyWire™
TranSiC™

TriFault Detect™
TRUECURRENT®*
µSerDes™

Serpes* UHC® Ultra FRFET™ UniFET™ VCX™ VisualMax™ VottagePlus™ XS™ Msens™ Misual™ UniFeT™ Misual™ Mi

* Trademarks of System General Corporation, used under license by Fairchild Semiconductor.

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. TO OBTAIN THE LATEST, MOST UP-TO-DATE DATASHEET AND PRODUCT INFORMATION, VISIT OUR WEBSITE AT http://www.fairchildsemi.com, FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OF CIRCUIT DESCRIBED HEREIN, NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

- Life support devices or systems are devices or systems which, (a) are
 intended for surgical implant into the body or (b) support or sustain
 life, and (c) whose failure to perform when properly used in
 accordance with instructions for use provided in the labeling, can be
 reasonably expected to result in a significant injury of the user.
- A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

ANTI-COUNTERFEITING POLICY

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, www.fairchildsemi.com, under Sales Support

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufacturers of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed applications, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from Fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handling and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address any warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition		
Advance Information	Formative / In Design	Datasheet contains the design specifications for product development. Specifications may change in any manner without notice.		
Preliminary First Production		Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.		
No Identification Needed Full Production		Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.		
Obsolete	Not In Production	Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only.		

Rev. 173

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Fairchild Semiconductor: MMPQ6700 MMPQ6700_Q