


Features


- Epitaxial Planar Die Construction
- Complementary NPN Type Available (DZT853)
- Ideally Suited for Automated Assembly Processes
- Ideal for Medium Power Switching or Amplification Applications
- **Lead Free By Design/RoHS Compliant (Note 1)**
- **"Green" Device (Note 2)**




SOT-223

Mechanical Data

- Case: SOT-223
- Case Material: Molded Plastic, "Green" Molding Compound. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020D
- Terminals: Finish — Matte Tin annealed over Copper Leadframe (Lead Free Plating). Solderable per MIL-STD-202, Method 208
- Marking Information: See Page 3
- Ordering Information: See Page 3
- Weight: 0.115 grams (approximate)



TOP VIEW



Schematic and Pin Configuration

Maximum Ratings @T_A = 25°C unless otherwise specified

| Characteristic | Symbol | Value | Unit |
|---|-----------------------------------|--------------------------|------|
| Collector-Base Voltage | V _{CB0} | -140 | V |
| Collector-Emitter Voltage | V _{CEO} | -100 | V |
| Emitter-Base Voltage | V _{EBO} | -6 | V |
| Continuous Collector Current | I _C | -5 | A |
| Peak Pulse Collector Current | I _{CM} | -10 | A |
| Power Dissipation | P _D | 1 (Note 3) 3 (Note 4) | W |
| Operating and Storage Temperature Range | T _J , T _{STG} | -55 to +150 | °C |

- Notes:
1. No purposefully added lead.
 2. Diodes Inc.'s "Green" policy can be found on our website at http://www.diodes.com/products/lead_free/index.php.
 3. Device mounted on FR-4 PCB, pad layout as shown on page 4.
 4. The power which can be dissipated, assuming the device is mounted in a typical manner on a PCB with copper equal to 4 square inch minimum.

Electrical Characteristics @T_A = 25°C unless otherwise specified

| Characteristic | Symbol | Min | Typ | Max | Unit | Test Condition |
|--------------------------------------|-------------------------------------|-----------------------------|-------------------------------|-----------------------------|----------|---|
| OFF CHARACTERISTICS | | | | | | |
| Collector-Base Breakdown Voltage | V _{(BR)CBO} | -140 | -165 | — | V | I _C = -100μA, I _E = 0 |
| Collector-Emitter Breakdown Voltage | V _{(BR)CEO} | -100 | -120 | — | V | I _C = -10mA*, I _B = 0 |
| Emitter-Base Breakdown Voltage | V _{(BR)EBO} | -6 | -9 | — | V | I _E = -100μA, I _C = 0 |
| Collector Cutoff Current | I _{CBO} | — | — | -50 -1 | nA μA | V _{CB} = -100V, I _E = 0 V _{CB} = -100V, I _E = 0, T _A = 100°C |
| Emitter Cutoff Current | I _{EBO} | — | — | -10 | nA | V _{EB} = -6V, I _C = 0 |
| ON CHARACTERISTICS | | | | | | |
| Collector-Emitter Saturation Voltage | V _{CE(SAT)} | — | -18 -70 -125 -260 | -50 -115 -220 -420 | mV | I _C = -100mA, I _B = -10mA* I _C = -1A, I _B = -100mA* I _C = -2A, I _B = -200mA* I _C = -4A, I _B = -400mA* |
| Base-Emitter Saturation Voltage | V _{BE(SAT)} | — | -960 | -1170 | mV | I _C = -4A, I _B = -400mA* |
| Base-Emitter Turn-On Voltage | V _{BE(ON)} | — | -880 | -1160 | mV | I _{CE} = -4A, V _{CE} = -1V* |
| DC Current Gain | h _{FE} | 100 100 50 30 — | 220 200 100 70 15 | — 300 — — — | — | I _C = -10mA, V _{CE} = -1V* I _C = -1A, V _{CE} = -1V* I _C = -3A, V _{CE} = -1V* I _C = -4A, V _{CE} = -1V* I _C = -10A, V _{CE} = -1V* |
| SMALL SIGNAL CHARACTERISTICS | | | | | | |
| Current Gain-Bandwidth Product | f _T | — | 125 | — | MHz | I _C = -100mA, V _{CE} = -10V, f = 50MHz |
| Output Capacitance | C _{obo} | — | 65 | — | pF | V _{CB} = -10V, f = 1MHz |
| SWITCHING CHARACTERISTICS | | | | | | |
| Switching Times | t _{on} t _{off} | — | 65 100 | — | ns | I _C = -2A, I _{B1} = -200mA I _{B2} = 200mA, V _{CC} = -10V |

*Measured under pulsed conditions. Pulse width = 300μs. Duty cycle ≤2%




Fig. 1 Power Dissipation vs. Ambient Temperature (Note 3)




Fig 2. Collector Current vs. Collector Emitter Voltage




Fig. 3 Typical DC Current Gain vs. Collector Current




Fig. 4 Collector-Emitter Saturation Voltage vs. Collector Current




Fig. 5 Base-Emitter Turn-On Voltage vs. Collector Current





Fig. 6 Base-Emitter Saturation Voltage vs. Collector Current

Ordering Information (Note 5)

| Device | Valid Marking Codes | Packaging | Shipping |
|-----------|---------------------|-----------|------------------|
| DZT953-13 | DZT953 | SOT-223 | 2500/Tape & Reel |
| DZT953-13 | PT06 | SOT-223 | 2500/Tape & Reel |

Notes: 5. Packaging Details as shown on page 4, or go to our website at <http://www.diodes.com/ap2007.pdf>.

Marking Information




DZT953 or PT06= Product Type Marking Code
 YM = Date Code Marking
 Y = Year ex: T = 2006
 M = Month ex: 9 = September

Date Code Key

| Year | 2006 | 2007 | 2008 | 2009 | 2010 | 2011 | 2012 |
|------|------|------|------|------|------|------|------|
| Code | T | U | V | W | X | Y | Z |


| Month | Jan | Feb | Mar | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec |
|-------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| Code | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | O | N | D |

Package Outline Dimensions



| SOT-223 | | | |
|----------------------|-------|------|------|
| Dim | Min | Max | Typ |
| A | 1.55 | 1.65 | 1.60 |
| A1 | 0.010 | 0.15 | 0.05 |
| b1 | 2.90 | 3.10 | 3.00 |
| b2 | 0.60 | 0.80 | 0.70 |
| C | 0.20 | 0.30 | 0.25 |
| D | 6.45 | 6.55 | 6.50 |
| E | 3.45 | 3.55 | 3.50 |
| E1 | 6.90 | 7.10 | 7.00 |
| e | — | — | 4.60 |
| e1 | — | — | 2.30 |
| L | 0.85 | 1.05 | 0.95 |
| Q | 0.84 | 0.94 | 0.89 |
| All Dimensions in mm | | | |

Suggested Pad Layout:



IMPORTANT NOTICE

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Diodes Incorporated does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

Diodes Incorporated products are not authorized for use as critical components in life support devices or systems without the expressed written approval of the President of Diodes Incorporated.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Diodes Incorporated:](#)

[DZT953-13](#)